

Explosion-protected LED flashlights



Lite-Ex PL 10e



- Ex-zone 0/20
- Ring switch
- High performance LED
- 64 lumen
- Rugged housing
- Diaphragm valve for pressure compensation
- Extremely lightweight

Explosion-protected LED flashlight (ATEX / IECEx zone 0/20)



Technical Data

General specifications

Bulb	High performance LED
Luminous intensity	3000 Lux (1 m distance)
Luminous flux	64 lumen

Electrical specifications

Battery type	3x LR03 / AAA (type-tested)
Operating duration	approx. 55 h (continuous operation)

Approvals and certificates

CE conformity	CE 0102
---------------	---------

Ambient conditions

Ambient temperature	-20 ... 50 °C (-4 ... 122 °F)
Storage temperature	-30 ... 60 °C (-22 ... 140 °F) (without batteries)

Mechanical specifications

Degree of protection	IP 65 IP 67 following EN/IEC 60529 (industrial standard)
Mass	approx. 120 g (with batteries)
Dimensions	147 mm x 36 mm

Data for application in connection with hazardous areas

EU-type examination certificate	EPS 16 ATEX 1 170 X
Marking	Ⓜ II 1G Ex ia IIC T4 Ga IP65 Ⓜ II 1D Ex ia IIC T130°C Da IP65

International approvals

IECEx approval	
IECEx certificate	IECEx EPS 16.0074X
IECEx marking	Ex ia IIC T4 Ga IP65 Ex ia IIC T130°C Da IP65

General information

Scope of delivery	Lite-Ex® PL 10e Batteries Hand strap Documentation
-------------------	---

Release date: 2022-01-10 Date of issue: 2022-01-10 Filename: 70138467_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0002
pa-info@us.pepperl-fuchs.com

Germany: +49 621 776 2222
pa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
pa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS