

300





SURPASSES ALL LED FLASHLIGHTS ON THE MARKET.

The Lite-Ex® PL 30e flashlight from ecom surpasses all other LED flashlights on the market.

The integrated 3 Watt LED, which is powered by 3 LR14 batteries, allows work to be conducted with extremely bright light for hours at a time.

In the new generation, a special reflector enables the illumination of larger surfaces.

The ergonomically designed, anti-static plastic housing ensures the flashlight fits perfectly in your hand and also provides excellent anti-slip protection.

The high IP65 protection rating prevents the permeation of dust and jet water. Use in harsh conditions is therefore not a problem.

SIMPLE AND RELIABLE TWIST MECHANISM

The switch-on mechanism is yet another outstanding feature - the flashlight is switched on via a sturdy rotating ring. This eliminates annoying malfunctions and repairs due to a faulty switch, thereby saving the user both time and money.

FEATURES

- Zone 0 / 20
- 1x high performance LED (3 Watt)
- 204 Lumen
- Ring switch
- Rugged housing
- High IP protection class IP65
- Diaphragm valve for pressure compensation

ACCESSORIES

	ARTIOLE NO	DDODUGT DECODIDATION
	ARTICLE NO.	PRODUCT DESCRIPTION
	A0002055 (Ex)	Leather holster
	ET002055 (£x)	Sealing kit
	ET002056 (£x)	Replacement lens
0	ET002059 (£x)	Ring switch

Lite-Ex® PL 30e LED FLASHLIGHT FOR ZONE 0 / 20

LED I LASTICIOTTI I ON ZONE 0 / 20

+ 51%
ADDITIONAL
LUMEN

SCOPE OF DELIVERY

- Lite-Ex® PL 30e
- Batteries
- Wrist strap
- User manual
- Ex-certificate
- EU Declaration of Conformity

EX DATA



© II 1 G Ex ia op is IIC T4 Ga IP65 © II 1 D Ex ia IIIC T130 °C Da IP65



Ex ia op is IIC T4 Ga IP65 Ex ia IIIC T130°C Da IP65

TECHNICAL DATA		
Ambient temperature	-20 °C +50 °C	
Storage temperature	-30 °C + 60 °C (without batteries)	
Power supply	3x LR 14 (type-tested)	
Light source	1x 3 Watt LED	
Luminosity	5,000 lux (at a distance of 1 m)	
Luminous flux	204 lumens	
Operating time	> 48 hrs (continuous operation)	
Dimensions	approx. 220 x 55 / 42 mm (L x Ø)	
Weight	approx. 530 g	
IP protection class	IP65	
ESD protection	Anti-static housing	
CE-designation	CE 0102	

6



EMEA

Germany (Headquarters) 1

ecom instruments GmbH Industriestraße 2 97959 Assamstadt Phone +49 62 94 42 24-0 Fax +49 62 94 42 24-100 sales@ecom-ex.com

ecom Benelux 2

ecom instruments BV
Watertoren 45c
3247 CL Dirksland, Netherlands
Phone +31 1 87 60 59 16
Fax +31 1 87 60 33 47
info.nl@ecom-ex.com
²also covering Belgium and Luxemburg

Eranco 3

Pepperl+Fuchs EURL
Division Mobile Safety
4 rue Ettore Bugatti
67201 Eckbolsheim (France)
Phone +33.3.88 76 46 84
mobile-safety@fr.pepperl-fuchs.com
3 also covering Algeria, Egypt, Morocco

Italy

ecom instruments srl Via Gandhi, 15 Galleria 20017 Rho (MI) Phone +39 02 93 90 92 16 Fax +39 02 93 90 62 97 info.it@ecom-ex.com

Switzerland

Pepperl+Fuchs AG Sägeweg 7 2557 Studen, Bern Phone +41 32 374 76 76 Fax +41 32 374 76 78 info.ch@ecom-ex.com

Nordics

ecom instruments GmbH Postbox 304 2970 Hørsholm Denmark Phone +45 28 252 575 info.nordics@ecom-ex.com

United Kingdom

ecom instruments ltd A310, The Wilton Centre, Redcar, TS10 4RF, United Kingdom Phone +44 1642 46 54 00 Fax +44 1642 46 54 02 info.uk@ecom-ex.com

Middle East

ecom instruments fze
P.O. Box 8918
Saif-Zone, Sharjah, UAE
Phone +971 6 5 57 34 30
Fax +971 6 5 57 34 31
info.uae@ecom-ex.com
4also covering Tunisia and Libya

Americas

USA

ecom instruments Inc. 1779 Westborough Drive, Suite 102 Katy, Texas 77449 Phone +1 281 496 59 30 Fax +1 281 496 23 21 sales.us@ecom-ex.com

Asia

South East Asia Pepperl+Fuchs Pte Ltd 15 Pioneer Turn P+F GDC Building Singapore 627577 Phone +65 6779 9078 info.sg@ecom-ex.com



05 / 2017 Subject to modifications